

Lay Flat Water Hose

- Hoses coil flat for easy storage
- Temperature range 5F to 170F
- Recommended fittings: Standard short shank aluminum, malleable or brass couplings



Heavy Duty Water Discharge Hose

- Premium quality PVC tube and cover, reinforced. Not intended for use as a fire hose
- May be coiled or racked when wet
- Excellent as a portable hydrant or relay supply line hose
- Resists kinking and twisting. High working pressure

Article NO.	Size	ID	OD	WP	BP	Weight
LF Series	Inch	mm		Bar		KG/100m
LF1	1	25.4	28.6	6	18	20
	1.5	38.1	41.3	6	18	30
	2	50.8	54	6	18	40
	2.5	63.5	67.1	6	18	53
	3	76.2	79.8	6	18	65
	4	101.6	105.2	6	18	90
	5	127	130.6	6	18	125
	6	152.4	156.4	6	18	150
	8	203.2	207.6	6	18	230

Medium Duty Water Discharge Hose

- Use for general purpose water discharge applications, ideal for use as a drip irrigation supply line
- Smooth tube provides low friction loss
- Lays straight with minimal elongation under pressure
- Homogeneous tube and cover construction eliminates separation

Article NO.	Size	ID	OD	WP	BP	Weight
LF Series	Inch	mm		Bar		KG/Roll
	1	25.4	28.6	4	12	15
	1.5	38.1	41.3	4	12	25
	2	50.8	54	4	12	35
	2.5	63.5	67.1	4	12	50
	3	76.2	79.8	4	12	60
	4	101.6	105.2	4	12	80
	5	127	130.6	4	12	100
	6	152.4	156.4	4	12	115
	8	203.2	207.6	4	12	190

Standard Duty Water Discharge Hose

- Use for general purpose water discharge applications, ideal for use as a drip irrigation supply line
- Smooth tube provides low friction loss
- Lays straight with minimal elongation under pressure
- Homogeneous tube and cover construction eliminates separation

Article NO.	Size	ID	OD	WP	BP	Weight
LF Series	Inch	mm		Bar		KG/100m
	1	25.4	27.8	3	9	14
	1.5	38.1	41.3	3	9	22.5
	2	50.8	54	3	9	32
	2.5	63.5	67.1	3	9	40
	3	76.2	79.8	3	9	50
	4	101.6	105.2	3	9	65
	5	127	130.6	3	9	85
	6	152.4	156.4	3	9	105
	8	203.2	207.6	3	9	180

Economy Duty Water Discharge Hose

- Use for general purpose water discharge applications, ideal for use as a drip irrigation supply line
- Smooth tube provides low friction loss
- Lays straight with minimal elongation under pressure
- Homogeneous tube and cover construction eliminates separation

Article NO.	Size	ID	OD	WP	BP	Weight
LF Series	Inch	mm		Bar		KG/100m
	1	25.4	27.8	2	6	12
	1.5	38	39.5	2	6	19
	2	50	52	2	6	27
	2.5	63	65	2	6	31
	3	76	78	2	6	39
	4	100	102	2	6	52
	5	127	129	2	6	85
	6	152	155	2	6	100
	8	203.2	207.6	2	6	170

HOSE POWER STATION